

Stability analysis of low-order combustion systems

Qing-Chang Zhong, Silviu-Iulian Niculescu and Anuradha M. Annaswamy

Abstract— In this paper, the stability conditions of second-order systems including a single-delay or two delays are considered. Such a model is frequently encountered in combustion systems. The stability analysis are vital for the safe operation of such systems. For the single-delay model, complete stability criteria are proposed; for the two-delay model, necessary conditions, sufficient conditions and necessary and sufficient conditions are obtained.

Index terms: combustion system; delay; stability analysis; dual-locus diagram

I. INTRODUCTION

In recent years, there are more and more applications involving the stability analysis of low-order systems including delay(s), apart from the stability analysis of general time-delay systems using time-domain approaches [1], [2], which in general only offers sufficient conditions and hence no clear information about how far away from the necessity these conditions are. However, there is a great need from engineering of such information. For example, the control of combustion systems [3], [4] relies on the stability analysis of a second-order system including two delays and a mass-spring-damper system controlled over communication networks [5], [6] relies on the stability analysis of a second-order system including one delay. It is crucial to understand the stability region of such systems so that the instability can be avoided.

Complete stability criteria were given in [6] for the mass-spring-damper system controlled over communication networks, where the control gain is assumed to be negative. In this paper, the result in [6] is extended to a more general case which allows the control gain to be positive as well. Hence, it can be used to analyze the stability of combustion systems [4], which can be modeled (linearized) as the following general second-order linear systems including two delays:

$$H_0(s) = s^2 + 2\zeta\alpha s + \alpha^2 + k_1 e^{-s\tau_1} + k_2 e^{-s\tau_2} = 0 \quad (1)$$

This research was partially supported by the EPSRC (Grant No. GR/N38190/1).

Qing-Chang Zhong is with the Dept. of Electrical & Electronic Engineering, Imperial College London, Exhibition Road, SW7 2BT, UK.

Silviu-Iulian Niculescu is with the Centre de Recherche de Royallieu, Universite de Technologie de Compiègne, BP 20529, 60205, Compiègne, France.

Anuradha M. Annaswamy is with the Adaptive Control Laboratory, Massachusetts Institute of Technology, Cambridge, MA 02139, USA.

under the hypothesis $0 < \tau_1 < \tau_2$. Here, τ_1 represents the connective delay (due to the transport lag from the supply to the burning plane of the flame), and τ_2 represents the propagation delay (velocity perturbations). Our objective in this paper is to find the stability condition of (1).

II. THE SINGLE-DELAY CASE

The single-delay case, e.g. when $k_2 = 0$ without loss of generality, was considered in [6] for negative gain k_1 using dual-locus diagram. Here, we extend the results obtained there to the case of $k_1 \in (-\infty, +\infty)$.

When $k_2 = 0$, the system (1) becomes

$$s^2 + 2\zeta\alpha s + \alpha^2 + k_1 e^{-s\tau_1} = 0. \quad (2)$$

The stability of (2) is equivalent to that of

$$1 + G(s)e^{-s\tau_1} = 0,$$

where

$$G(s) = \frac{k_1}{s^2 + 2\zeta\alpha s + \alpha^2}.$$

The magnitude response of $G(s)$ is

$$|G(j\omega)| = \frac{|k_1|}{\sqrt{(\alpha^2 - \omega^2)^2 + 4\zeta^2\alpha^2\omega^2}}.$$

For $0 < \zeta < \frac{1}{\sqrt{2}}$, the peak of $|G(j\omega)|$ is



$$|G(j\omega)|_p = \frac{|k_1|}{2\zeta\alpha^2\sqrt{1-\zeta^2}}$$

at $\omega_p = \alpha\sqrt{1-2\zeta^2}$; for $\zeta \geq \frac{1}{\sqrt{2}}$, the peak of $|G(j\omega)|$ is

$$|G(j\omega)|_p = \frac{|k_1|}{\alpha^2}$$

at $\omega_p = 0$. In other words, the magnitude response has two kinds of shapes, as shown in Figure 1. In one case ($0 < \zeta < \frac{1}{\sqrt{2}}$), there is one peak and in the other case ($\zeta \geq \frac{1}{\sqrt{2}}$) the magnitude response is monotonically decreasing. It is worth noting that the step response has a peak if $\zeta < 1$, which should not be confused with the case of frequency responses.

According to the well-known small-gain theorem, the system (2) is delay-independently stable when $|G(j\omega)|_p < 1$. This provides two stability conditions: (i) $|k_1| < \alpha^2$ if $\zeta \geq \frac{1}{\sqrt{2}}$; (ii) $|k_1| < 2\zeta\alpha^2\sqrt{1-\zeta^2}$ if $0 < \zeta < \frac{1}{\sqrt{2}}$. In these cases, the magnitude curves do not intersect with the straight line "1" shown in Figure 1 (a) and (b) and

(a) $0 < \zeta < \frac{1}{\sqrt{2}}$ (b) $\zeta \geq \frac{1}{\sqrt{2}}$ Fig. 1. The magnitude response of $G(s)$

hence the system is delay-independently stable. Naturally, another two cases are: the magnitude curve intersects with the straight line twice at ω_A and then at ω_B (this only happens when $0 < \zeta < \frac{1}{\sqrt{2}}$) or only once at ω_C . The stability criteria for these two cases will be analyzed below:

Case 1: $|k_1| \geq \alpha^2$

The magnitude curve starts above '1', see Figure 1 (a) and (b), and there is only one intersection at

$$\omega_C = \alpha \sqrt{1 - 2\zeta^2 + \sqrt{4\zeta^4 - 4\zeta^2 + k_1^2/\alpha^4}}, \quad (3)$$

which is the positive solution of $|G(j\omega)| = 1$, i.e. of

$$(\alpha^2 - \omega^2)^2 + 4\zeta^2 \alpha^2 \omega^2 = k_1^2.$$

If k_1 is positive, i.e. if $k_1 \geq \alpha^2$, then (2) is delay-independently stable if

$$\omega_C \tau_1 + \arctan \frac{2\zeta \alpha \omega_C}{\alpha^2 - \omega_C^2} < \pi.$$

Since there is only one intersection ω_C , there is only one delay interval so that the system is stable. If k_1 is negative,




Fig. 2. The dual-locus diagram of the single-delay system

i.e. if $k_1 \leq -\alpha^2$, then (2) is always unstable because there is no phase margin left for the delay term.

Case 2: $0 < \zeta < \frac{1}{\sqrt{2}}$ and $\alpha^2 > |k_1| \geq 2\zeta\alpha^2\sqrt{1-\zeta^2}$

The magnitude curve starts above '1' but the peak stays below '1', see Figure 1(a). There are two intersections with the straight line '1' at

$$\omega_A = \alpha \sqrt{1 - 2\zeta^2 - \sqrt{4\zeta^4 - 4\zeta^2 + k_1^2/\alpha^4}}$$

and

$$\omega_B = \alpha \sqrt{1 - 2\zeta^2 + \sqrt{4\zeta^4 - 4\zeta^2 + k_1^2/\alpha^4}},$$

which are the positive solutions of $|G(j\omega)| = 1$, i.e. of

$$(\alpha^2 - \omega^2)^2 + 4\zeta^2 \alpha^2 \omega^2 = k_1^2.$$

The dual-locus diagram in this case, $L_1(s) = G(s)$ and $L_2(s) = e^{\tau_1 s}$, is shown in Figure 2 for $\omega = 0 \sim +\infty$. A similar dual-locus diagram was used in [7], but here we can recover the phase angle (equal to the phase difference between the two loci) in the Nyquist plot. The locus L_1 starts inside the locus L_2 and moves outside of L_2 at ω_A then moves inside L_2 at ω_B . For positive k_1 , L_1 (the solid one) starts on the positive real axis; for negative k_1 , L_1 (the dashed one) starts on the negative real axis. The stability will be analyzed below according to the sign of k_1 :

(i) k_1 is positive

When L_1 arrives at $\omega = \omega_A$, the phase difference ϕ_A (between L_1 and L_2) is

$$\phi_A = -\arctan \frac{2\zeta \alpha \omega_A}{\alpha^2 - \omega_A^2} - (\omega_A \tau_1).$$

There exists a unique nonnegative integer i such that the phase difference ϕ_A biased by $2i\pi$ belongs to $(-\pi, \pi)$, i.e.,

$$-\pi < \phi_A + 2i\pi < \pi. \quad (4)$$

A different i is called a different cycle, which starts above the negative real axis and ends below the negative real axis (i.e. the negative real axis is split). When $i = 0$, the above

inequality includes the principle half cycle $-\pi < \phi_A \leq 0$. According to the Nyquist criteria, the system (2) is stable if and only if the phase difference ϕ_B between L_1 and L_2 , when L_1 arrives at $\omega = \omega_B$, is still in the same cycle, i.e.,

$$-\pi < -\arctan \frac{2\zeta\alpha\omega_B}{\alpha^2 - \omega_B^2} - (\omega_B\tau_1) + 2i\pi. \quad (5)$$

Otherwise, the Nyquist plot encircles the point $(-1, 0)$, which implies the instability. The inequalities (4) and (5) together provide the following delay intervals to guarantee the system stability:

$$\frac{1}{\omega_A}(2i\pi - \pi - \arctan \frac{2\zeta\alpha\omega_A}{\alpha^2 - \omega_A^2}) < \tau_1 < \frac{1}{\omega_B}(2i\pi + \pi - \arctan \frac{2\zeta\alpha\omega_B}{\alpha^2 - \omega_B^2}), \quad (6)$$

where $i = 0, 1, 2, \dots$ till the right side is no longer larger than the left.

(ii) k_1 is negative

In this case, due to the negativeness of k_1 , there is an extra phase shift $-\pi$, i.e.,

$$\phi_A = -\pi - \arctan \frac{2\zeta\alpha\omega_A}{\alpha^2 - \omega_A^2} - (\omega_A\tau_1).$$

Due to this extra phase shift, the principle cycle (corresponding to $i = 0$) becomes $(-\pi, -3\pi)$ and hence there exists a unique nonnegative integer i such that the biased phase shift, $\phi_A + 2i\pi$, satisfies

$$-3\pi < \phi_A + 2i\pi < -\pi. \quad (7)$$

The system (2) is stable if and only if the phase difference ϕ_B between L_1 and L_2 , when L_1 arrives at $\omega = \omega_B$, is still in the same cycle, i.e.,

$$-3\pi < -\pi - \arctan \frac{2\zeta\alpha\omega_B}{\alpha^2 - \omega_B^2} - (\omega_B\tau_1) + 2i\pi. \quad (8)$$

The inequalities (7) and (8) together provide the following delay intervals to guarantee the system stability:

$$\frac{1}{\omega_A}(2i\pi - \arctan \frac{2\zeta\alpha\omega_A}{\alpha^2 - \omega_A^2}) < \tau_1 < \frac{1}{\omega_B}(2i\pi + 2\pi - \arctan \frac{2\zeta\alpha\omega_B}{\alpha^2 - \omega_B^2}), \quad (9)$$

where $i = 0, 1, 2, \dots$ till the right side is no longer larger than the left. This condition, although in different form, is equivalent to that obtained in [6].

In summary, the following three lemmas hold:

Lemma 1. *The system (2) is always unstable if $-\frac{k_1}{\alpha^2} \geq 1$. See region R_U in Figure 3.*

Lemma 2. *The system (2) is delay-independently stable, see region R_I in Figure 3, if one of the following conditions hold:*

- (i) $|k_1| < \alpha^2$ if $\zeta \geq \frac{1}{\sqrt{2}}$;
- (ii) $|k_1| < 2\zeta\alpha^2\sqrt{1-\zeta^2}$ if $0 < \zeta < \frac{1}{\sqrt{2}}$.

Lemma 3. *The system (2) is delay-dependently stable if one of the following conditions hold:*

(i) $0 < \zeta < \frac{1}{\sqrt{2}}$ and $1 > -\frac{k_1}{\alpha^2} \geq 2\zeta\sqrt{1-\zeta^2}$. See region R_A in Figure 3. The delay intervals guaranteeing the stability are given in (9);

(ii) $0 < \zeta < \frac{1}{\sqrt{2}}$ and $-1 < -\frac{k_1}{\alpha^2} \leq -2\zeta\sqrt{1-\zeta^2}$. See region R_B in Figure 3. The delay intervals guaranteeing the stability are given in (6);




Fig. 3. The stability regions of the single-delay system

(iii) $-\frac{k_1}{\alpha^2} \leq -1$ and $0 \leq \tau_1 < \frac{1}{\omega_C}(\pi - \arctan \frac{2\zeta\alpha\omega_C}{\alpha^2 - \omega_C^2})$ with ω_C given in (3). See region R_C in Figure 3.

III. MAIN RESULTS

A. Sufficient conditions

The system (1) can be reformulated as

$$1 + M(s)e^{-s\tau_1} = 0$$

where

$$M(s) = \frac{k_1 + k_2e^{-s(\tau_2-\tau_1)}}{s^2 + 2\zeta\alpha s + \alpha^2}.$$

Since $|e^{-s(\tau_2-\tau_1)}| = 1$ for any $\omega \in (-\infty, +\infty)$, $M(s)$ has the following upper envelope

$$M_e(s) = \frac{|k_1| + |k_2|}{s^2 + 2\zeta\alpha s + \alpha^2}.$$

According to the result in the last section, $M_e(s)$ has a peak value of

$$M_{ep} = \frac{|k_1| + |k_2|}{2\zeta\alpha^2\sqrt{1-\zeta^2}}$$

for $0 < \zeta < \frac{1}{\sqrt{2}}$ or a peak value of

$$M_{ep} = \frac{|k_1| + |k_2|}{\alpha^2}$$

for $\zeta \geq \frac{1}{\sqrt{2}}$. According to the small-gain theorem, the following theorem holds:

Theorem 1. *The system (1) is delay-independently stable if one of the following conditions hold:*

- (i) $|k_1| + |k_2| < \alpha^2$ if $\zeta \geq \frac{1}{\sqrt{2}}$;
- (ii) $|k_1| + |k_2| < 2\zeta\alpha^2\sqrt{1-\zeta^2}$ if $0 < \zeta < \frac{1}{\sqrt{2}}$.

These conditions can be depicted as shown in Figure 4. The smaller the damping ratio, the smaller the stability region. When $\zeta \geq \frac{1}{\sqrt{2}}$, the stability region does not change.




Fig. 4. The delay-independent stability region of (1)

B. Necessary conditions

Lemma 4. [8], [9] Consider the following quasipolynomial

$$H(s) = \sum_{l=1}^r \sum_{i=0}^n h_{il} s^{n-i} e^{\tau_l s},$$

where $\tau_1 < \tau_2 < \dots < \tau_r$, $\tau_r + \tau_1 > 0$ and the main term $h_{0r} \neq 0$ (corresponding to the largest τ_l and the highest degree of s).

If $H(s)$ is stable, then the derivative of $H(s)$ w.r.t s , $H'(s)$, is also a stable quasipolynomial.

This lemma will be used to derive a necessary condition for the combustion system (1). Denote

$$H_1(s) = (s^2 + 2\zeta\alpha s + \alpha^2)e^{s\tau_2} + k_1 e^{-s(\tau_1 - \tau_2)} + k_2,$$

then the following result holds:

Theorem 2. The system given in (1) is unstable if $-k_1(\tau_2 - \tau_1) \geq \alpha^2\tau_2 + 2\zeta\alpha$.

The system given in (1) is delay-dependently stable only if one of the following conditions hold:

- (i) $|k_1| < \frac{(2\zeta + \alpha\tau_2)\alpha}{\tau_2 - \tau_1}$ and $\sqrt{2}(\tau_2\zeta\alpha + 1) \geq \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}$;
- (ii) $|k_1| < \frac{2(\tau_2\zeta\alpha + 1)}{\tau_2(\tau_2 - \tau_1)} \cdot \sqrt{\alpha\tau_2(2\zeta + \alpha\tau_2) - (\tau_2\zeta\alpha + 1)^2}$ and $\sqrt{2}(\tau_2\zeta\alpha + 1) < \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}$;
- (iii) $\sqrt{2}(\tau_2\zeta\alpha + 1) < \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}$ and $\frac{\alpha^2\tau_2 + 2\zeta\alpha}{\tau_2 - \tau_1} > -k_1 \geq 2\frac{\zeta\alpha\tau_2 + 1}{\tau_2(\tau_2 - \tau_1)}\sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2 - (\zeta\alpha\tau_2 + 1)^2}$ and $\frac{1}{\hat{\omega}_A}(2i\pi - \arctan \frac{2(\zeta\alpha\tau_2 + 1)\hat{\omega}_A}{\alpha^2\tau_2 + 2\zeta\alpha - \tau_2\hat{\omega}_A^2}) < \tau_1 < \frac{1}{\hat{\omega}_B}(2i\pi + 2\pi - \arctan \frac{2(\zeta\alpha\tau_2 + 1)\hat{\omega}_B}{\alpha^2\tau_2 + 2\zeta\alpha - \tau_2\hat{\omega}_B^2})$;
- (iv) $\sqrt{2}(\tau_2\zeta\alpha + 1) < \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}$ and $-\frac{\alpha^2\tau_2 + 2\zeta\alpha}{\tau_2 - \tau_1} < -k_1 \leq -2\frac{\zeta\alpha\tau_2 + 1}{\tau_2(\tau_2 - \tau_1)}\sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2 - (\zeta\alpha\tau_2 + 1)^2}$ and $\frac{1}{\hat{\omega}_A}(2i\pi - \pi - \arctan \frac{2(\zeta\alpha\tau_2 + 1)\hat{\omega}_A}{\alpha^2\tau_2 + 2\zeta\alpha - \tau_2\hat{\omega}_A^2}) < \tau_1 < \frac{1}{\hat{\omega}_B}(2i\pi + \pi - \arctan \frac{2(\zeta\alpha\tau_2 + 1)\hat{\omega}_B}{\alpha^2\tau_2 + 2\zeta\alpha - \tau_2\hat{\omega}_B^2})$;
- (v) $-\frac{k_1(\tau_2 - \tau_1)}{\alpha^2\tau_2 + 2\zeta\alpha} \leq -1$ and $0 \leq \tau_1 < \frac{1}{\hat{\omega}_C}(\pi - \arctan \frac{2(\zeta\alpha\tau_2 + 1)\hat{\omega}_C}{\alpha^2\tau_2 + 2\zeta\alpha - \tau_2\hat{\omega}_C^2})$.

The above-mentioned $\hat{\omega}_A$, $\hat{\omega}_B$ and $\hat{\omega}_C$ are given below when the corresponding conditions hold:

$$\begin{aligned} \hat{\omega}_A &= \frac{1}{\tau_2} \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2 - 2(\zeta\alpha\tau_2 + 1)^2(1 + \sqrt{1 - \frac{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}{(\zeta\alpha\tau_2 + 1)^2} + \frac{k_1^2\tau_2^2(\tau_2 - \tau_1)^2}{4(\zeta\alpha\tau_2 + 1)^4}}), \\ \hat{\omega}_B &= \frac{1}{\tau_2} \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2 - 2(\zeta\alpha\tau_2 + 1)^2(1 - \sqrt{1 - \frac{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}{(\zeta\alpha\tau_2 + 1)^2} + \frac{k_1^2\tau_2^2(\tau_2 - \tau_1)^2}{4(\zeta\alpha\tau_2 + 1)^4}}), \\ \hat{\omega}_C &= \frac{1}{\tau_2} \sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2 - 2(\zeta\alpha\tau_2 + 1)^2(1 - \sqrt{1 - \frac{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}{(\zeta\alpha\tau_2 + 1)^2} + \frac{k_1^2\tau_2^2(\tau_2 - \tau_1)^2}{4(\zeta\alpha\tau_2 + 1)^4}}). \end{aligned}$$

Proof. Obviously, $H_1(s)$ holds the same stability as $H_0(s)$. According to Lemma 4, if $H_1(s)$ is stable, then

$$H_1'(s) = (2s + 2\zeta\alpha + \tau_2(s^2 + 2\zeta\alpha s + \alpha^2) + k_1(\tau_2 - \tau_1)e^{-s\tau_1})e^{s\tau_2}$$

is also stable, which means the following quasipolynomial is stable:

$$H_2(s) = s^2 + 2(\zeta\alpha + \frac{1}{\tau_2})s + (\frac{2\zeta}{\tau_2} + \alpha)\alpha + k_1(1 - \frac{\tau_1}{\tau_2})e^{-s\tau_1}.$$

This is the single-delay system of which the complete sta-

bility criteria was given in the last section. Directly using those results with the following substitutions completes the proof:

$$\begin{aligned} \alpha &\leftarrow: \sqrt{\alpha^2 + \frac{2\zeta\alpha}{\tau_2}} \\ \zeta &\leftarrow: \frac{\zeta\alpha\tau_2 + 1}{\sqrt{\alpha^2\tau_2^2 + 2\zeta\alpha\tau_2}} \\ k_1 &\leftarrow: k_1(1 - \frac{\tau_1}{\tau_2}) \end{aligned}$$

$$\frac{k_1}{\alpha^2} \leftarrow: \frac{k_1(\tau_2 - \tau_1)}{\alpha^2 \tau_2 + 2\zeta\alpha}$$

$$\arctan \frac{2\zeta\alpha\omega_C}{\alpha^2 - \omega_C^2} \leftarrow: \arctan \frac{2(\zeta\alpha\tau_2 + 1)\omega_C}{\alpha^2 \tau_2 + 2\zeta\alpha - \tau_2 \omega_C^2}$$

□

C. Necessary and sufficient conditions

Lemma 5. *The argument of $k_1 + k_2 e^{-j\omega(\tau_2 - \tau_1)}$ is monotonically decreasing with respect to $\omega : 0 \rightarrow +\infty$ iff $|k_2| \geq |k_1|$. Hence, so is the argument of $M(j\omega)$ if $|k_2| \geq |k_1|$.*

Proof. Denote the argument of $k_1 + k_2 e^{-j\omega(\tau_2 - \tau_1)}$ by ϕ_e and $\tau_2 - \tau_1$ by Δ , then

$$\phi_e(\omega) = \arctan \frac{-k_2 \sin \Delta\omega}{k_1 + k_2 \cos \Delta\omega}.$$

Differentiate ϕ_e with respect to ω , we have

$$\frac{d\phi_e}{d\omega} = -\Delta \cdot \frac{k_1 k_2 \cos \Delta\omega + k_2^2}{(k_1 + k_2 \cos \Delta\omega)^2 + k_2^2 \sin^2 \Delta\omega}.$$

Since $\Delta = \tau_2 - \tau_1 > 0$, $\frac{d\phi_e}{d\omega} \leq 0$ if and only if

$$k_1 k_2 \cos \Delta\omega + k_2^2 \geq 0,$$

which is equivalent to

$$|k_2| \geq |k_1|.$$

It is easy to check that the other part of the argument of $M(j\omega)$ is always monotonically decreasing for $\omega : 0 \rightarrow +\infty$. Hence, so is the argument of $M(j\omega)$. This completes the proof. □

This condition can be depicted as the shadowed area shown in Figure 5. If this condition is satisfied, then the Nyquist curve of $k_1 + k_2 e^{-j\omega\Delta}$ encircles the origin for indefinite times. In the sequel, we will analyze the stability when this condition is met. Another important condition is that if $|k_1 + k_2| < \alpha^2$ or not. Using these two conditions, the shadowed area is split into 4 regions (R_U , R_A , R_B and R_C) as shown in Figure 5. The typical dual-locus diagrams with $L_1(s) = M(s)$ and $L_2(s) = e^{\tau_1 s}$ are shown in Figure 6 for these regions. When $k_2 > 0$, the locus starts on the positive real axis; when $k_2 < 0$, the locus starts on the negative real axis. If $|k_1 + k_2| < \alpha^2$, the locus starts inside of the unit cycle; if $|k_1 + k_2| > \alpha^2$, the locus starts outside of the unit cycle. All locus approaches the origin when $\omega \rightarrow +\infty$. Hence, the locus intersects with the unit cycle for finite times: odd times if $|k_1 + k_2| > \alpha^2$ or even times if $|k_1 + k_2| < \alpha^2$. Denote the first outgoing (w.r.t. the unit cycle) crossing frequency by ω_1 and the rest ingoing and outgoing frequencies by $\omega_2, \dots, \omega_{2r-1}$ and ω_{2r} . The locus crosses the unit cycle for r rounds. If $|k_1 + k_2| > \alpha^2$, the first crossing is ingoing and the corresponding crossing




Fig. 5. The stability regions of (1). The dotted box is the delay-independent stability region (see Figure 4)




Fig. 6. Dual-locus diagrams of (1) when $|k_2| \geq |k_1|$

frequency is denoted by ω_0 . Apparently, these frequencies are the ordered positive solutions of the equation

$$|M(j\omega)| = 1,$$

i.e. of

$$k_1^2 + 2k_1 k_2 \cos \Delta\omega + k_2^2 = (\alpha^2 - \omega^2)^2 + 4\zeta^2 \alpha^2 \omega^2.$$

Bearing in mind, when the conditions given in Theorem 1 are satisfied there will be no crossing. The locus L_1 remains inside of the locus L_2 .

If there is no delay τ_1 (i.e. $\tau_1 = 0$), then the system is stable if and only if the locus does not encircle the point $(-1, 0)$. In other words, the crossings at ω_{2i-1} and ω_{2i} are in the same cycle c_i . When $\tau_1 \neq 0$, the phase shift due to τ_1 should be considered. Using the similar arguments in the previous section, the following results can be obtained.

Theorem 3. *When $|k_2| \geq |k_1|$, the system (1) is unstable for any delays $\tau_1 > 0$ and $\tau_2 > 0$ if $k_1 + k_2 \leq -\alpha^2$. See region R_U in Figure 5.*

Theorem 4. *When $|k_2| \geq |k_1|$, the system (1) is (delay-dependently) stable if one of the following conditions hold:*

- (i) $0 > k_1 + k_2 > -\alpha^2$ and

there exists a $c_i \geq 0$ for each $i = 1, 2, \dots, r$ such that

$$\frac{1}{\omega_{2i-1}}(2c_i\pi + \phi_e(\omega_{2i-1}) - \arctan \frac{2\zeta\alpha\omega_{2i-1}}{\alpha^2 - \omega_{2i-1}^2}) < \tau_1 < \frac{1}{\omega_{2i}}(2c_i\pi + 2\pi + \phi_e(\omega_{2i}) - \arctan \frac{2\zeta\alpha\omega_{2i}}{\alpha^2 - \omega_{2i}^2}).$$

See region R_A in Figure 5;

(ii) $0 < k_1 + k_2 < \alpha^2$ and

there exists a $c_i \geq 0$ for each $i = 1, 2, \dots, r$ such that

$$\frac{1}{\omega_{2i-1}}(2c_i\pi - \pi + \phi_e(\omega_{2i-1}) - \arctan \frac{2\zeta\alpha\omega_{2i-1}}{\alpha^2 - \omega_{2i-1}^2}) < \tau_1 < \frac{1}{\omega_{2i}}(2c_i\pi + \pi + \phi_e(\omega_{2i}) - \arctan \frac{2\zeta\alpha\omega_{2i}}{\alpha^2 - \omega_{2i}^2}).$$

See region R_B in Figure 5;

(iii) $k_1 + k_2 > \alpha^2$ and

$0 \leq \tau_1 < \frac{1}{\omega_0}(\pi + \phi_e(\omega_0) - \arctan \frac{2\zeta\alpha\omega_0}{\alpha^2 - \omega_0^2})$ and

there exists a $c_i \geq 0$ for each $i = 1, 2, \dots, r$ such that

$$\frac{1}{\omega_{2i-1}}(2c_i\pi - \pi + \phi_e(\omega_{2i-1}) - \arctan \frac{2\zeta\alpha\omega_{2i-1}}{\alpha^2 - \omega_{2i-1}^2}) < \tau_1 < \frac{1}{\omega_{2i}}(2c_i\pi + \pi + \phi_e(\omega_{2i}) - \arctan \frac{2\zeta\alpha\omega_{2i}}{\alpha^2 - \omega_{2i}^2}).$$

See region R_C in Figure 5.

The axis k_1/α^2 in Figure 5 has been cut into four pieces corresponding to the four regions. This is exactly the results given in lemmas 1-3. Hence, one might expect that the four regions shown in Figure 5 can be extended, at least, to the axis k_1/α^2 . However, we haven't found solid evidence to support this.

IV. CONCLUSION

In this paper, the stability of combustion systems modeled as a second-order including one or two delays are analyzed. When there is only one delay, the complete stability criteria have been given; when there are two delays in the model, necessary conditions, sufficient conditions and necessary and sufficient conditions are obtained.

REFERENCES

- [1] K. Gu and S.-I. Niculescu, "Additional dynamics in transformed time-delay systems," *IEEE Trans. Automat. Control*, vol. 45, no. 3, pp. 572–575, 2000.
- [2] —, "Further remarks on additional dynamics in various model transformations of linear delay systems," *IEEE Trans. Automat. Control*, vol. 46, no. 3, pp. 497–500, 2001.
- [3] S.-I. Niculescu, *Delay effects on stability: A robust control approach*, ser. LNCIS. Springer-Verlag, Heidelberg, Germany, 2001, vol. 269.
- [4] S.-I. Niculescu, A. Annaswamy, J. Hathout, and A. Ghoniem, "On time-delay induced instabilities in low order combustion systems," in *Proc. 1st IFAC Symp. Syst. Struct. Contr.*, Prague, Czech Republic, 2001.
- [5] Y. Chen and K. Moore, "Analytical stability bound for delayed second-order systems with repeating poles using Lambert function W," *Automatica*, vol. 38, no. 5, pp. 891–895, 2002.
- [6] Q.-C. Zhong, "Robust stability analysis of simple systems controlled over communication networks," *Automatica*, vol. 39, no. 7, pp. *, 2003.
- [7] C. Chen and I. Haas, "An extension of Oppelt's stability criterion based on the method of two hodographs," *IEEE Trans. Automat. Control*, vol. 10, no. 1, pp. 99–102, 1965.
- [8] J. Moreno, "An extension of Lucas theorem to entire functions," in *Proc. of 1st IFAC Workshop on Linear Time Delay Systems*, Grenoble, France, 1998, pp. 159–163.
- [9] V. Kharitonov, S.-I. Niculescu, J. Moreno, and W. Michiels, "Some remarks on static output feedback stabilization," 2003.